

Safety Data Sheet TEAK 3



Safety Data Sheet dated 30/7/2019, version 2
Regulation (EU) 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Identification of the mixture:

Trade name: TEAK 3
Trade code: 6813.001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Wood preservative

1.3. Details of the supplier of the safety data sheet

Company:

BOERO BARTOLOMEO S.p.A. - Via Macaggi 19 - 16121 Genova - Tel. +39 010 55001 - Fax +39 010 5500305 - CF/P. IVA/REG. IMPRESE DI GENOVA 00267120103

Brand Veneziani TM used Under License of Colorificio Zetagi S.r.l.

Competent person responsible for the safety data sheet:

sicurezzaprodotti@boero.it

1.4. Emergency telephone number

BOERO BARTOLOMEO S.p.A. - Tel.+39 010 55001

opening hours: Monday - Tuesday 9.00 am - 5.00 pm

UK: in an emergency the enquirer should call NHS 111/24/Direct (free-to-call medical helplines) or a doctor.

MALTA: tel. 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Flam. Liq. 3, H226 Flammable liquid and vapour.

STOT SE 3, H336 May cause drowsiness or dizziness.

STOT RE 1, H372 Causes damage to organs through prolonged or repeated exposure.

Asp. Tox. 1, H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2, H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

6813.001/2

Page n. 1 of 12

Safety Data Sheet

TEAK 3

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P370+P378 In case of fire use CO₂ or chemical powder. Never use water.

P501 Dispose of contents/container according to local regulations.

Special Provisions:

PACK1 The packing must be featured by a safety lock for children.

PACK2 The packing must have tactile indications of danger for blind people.

Contains

xylene [4]

ethylbenzene

Hydrocarbons, C₉-C₁₂, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

Adverse physicochemical, human health and environmental effects:

The main adverse physical-chemical effects for human health and the environment are listed in accordance with Sections 9 to 12 of the safety data sheet

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 80% - < 90% Hydrocarbons, C₉-C₁₂, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

EC: 919-446-0

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

STOT SE 3 H336 May cause drowsiness or dizziness.

Flam. Liq. 3 H226 Flammable liquid and vapour.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

DECLP (CLP)*

>= 9% - < 10% 2-butoxyethanol; ethylene glycol monobutyl ether

REACH No.: 01-2119475108-36-XXXX, Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Irrit. 2 H315 Causes skin irritation.

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

6813.001/2

Page n. 2 of 12

Safety Data Sheet

TEAK 3

Acute Tox. 4 H332 Harmful if inhaled.

$\geq 0.01\%$ - $< 0.1\%$ ethylbenzene

Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

STOT RE 2 H373 H373.5

Acute Tox. 4 H332 Harmful if inhaled.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

$\geq 0.01\%$ - $< 0.1\%$ xylene [4]

REACH No.: 01-2119488216-32-XXXX, CAS: 1330-20-7, EC: 215-535-7

Flam. Liq. 3 H226 Flammable liquid and vapour.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Acute Tox. 4 H332 Harmful if inhaled.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Irrit. 2 H315 Causes skin irritation.

$\geq 0.01\%$ - $< 0.1\%$ 1,2,4-trimethylbenzene

Index number: 601-043-00-3, CAS: 95-63-6, EC: 202-436-9

Flam. Liq. 3 H226 Flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Acute Tox. 4 H332 Harmful if inhaled.

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

Give nothing to eat or drink.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

6813.001/2

Page n. 3 of 12

Safety Data Sheet

TEAK 3

- 4.2. Most important symptoms and effects, both acute and delayed
May be fatal if swallowed and enters airways.
- 4.3. Indication of any immediate medical attention and special treatment needed
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Treatment:
None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
Suitable extinguishing media:
In case of fire use CO2 or chemical powder. Never use water.
Extinguishing media which must not be used for safety reasons:
Do not use water jets
None in particular.
- 5.2. Special hazards arising from the substance or mixture
Avoid inhaling the fumes.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Adequately ventilated premises.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Always keep the containers tightly closed.

Safety Data Sheet

TEAK 3

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Adequately ventilated premises.

7.3. Specific end use(s)

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

EU - TWA(8h): 290 mg/m³, 50 ppm - STEL: 580 mg/m³, 100 ppm

2-butoxyethanol; ethylene glycol monobutyl ether - CAS: 111-76-2

EU - TWA(8h): 98 mg/m³, 20 ppm - STEL: 246 mg/m³, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

AGS - TWA(8h): 200 mg/m³ - STEL((15 min)): 450 mg/m³

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

VLE1 - TWA(8h): 442 mg/m³, 100 ppm

VLE - STEL: 884 mg/m³, 200 ppm

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

AGS - TWA(8h): 221 mg/m³ - STEL((15 min)): 442 mg/m³ - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

AGS - TWA(8h): 221 mg/m³ - STEL((15 min)): 442 mg/m³ - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)

VLE1 - TWA(8h): 211 mg/m³, 50 ppm

VLE - STEL: 442 mg/m³, 100 ppm - Notes: Skin

1,2,4-trimethylbenzene - CAS: 95-63-6

EU - TWA(8h): 100 mg/m³, 20 ppm

DNEL Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/L

6813.001/2

Page n. 5 of 12

Safety Data Sheet

TEAK 3

Target: Marine water - Value: 0.327 mg/L
Target: Freshwater sediments - Value: 12.46 mg/kg
Target: Marine water sediments - Value: 12.46 mg/kg
Target: Microorganisms in sewage treatments - Value: 6.58 mg/L

Biological Exposure Index

ethylbenzene - CAS: 100-41-4

Value: 1.50 mg/L - medium: Blood - Sampling Period: DU

Value: 2 ppm - medium: Air at the end of exhalation - Sampling Period: A

Value: 1.50 gg creatinina - medium: Urine - Biological Indicator: 78 - Sampling Period:
End of turn; End of working week

xylene [4] - CAS: 1330-20-7

Value: 1.50 mg/L - medium: Blood - Sampling Period: End of turn

Value: 1.50 gg creatinina - medium: Blood - Sampling Period: End of turn

8.2. Exposure controls

Eye protection:

Use goggles/face mask certified UNI EN 166.

Protection for skin:

Suitable protective clothing is required for complete skin protection: for example coveralls with long sleeves and trousers, rubber boots and apron, etc., according to UNI EN 14325.

Protection for hands:

Use protective gloves: waterproof rubber gloves certified UNI EN 374. Nitrile gloves provide good protection. Use care in selecting a penetration time of the gloves longer than the foreseen usage time.

Respiratory protection:

Use adequate protective respiratory equipment: a carbon filter mask with filters certified UNI EN 149 or dust masks certified UNI EN 140. Filters of types A and P types may be considered.

Thermal Hazards:

None

Environmental exposure controls:

See sections 6 and 13

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance :	liquid
Odour:	N.A.
Colour:	colourless
pH:	N.A.
Melting point / freezing point:	N.A.
Boiling point (°C):	bp>35 °C
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	40 °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Specific gravity (Kg/L) 20°C :	0.0000
Methodology:	

6813.001/2

Page n. 6 of 12

Safety Data Sheet

TEAK 3

Solubility in water: N.A.
Lipid solubility: N.A.
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Kinematic viscosity at 40°C (mm²/s): 14 < kv ≤ 20,5
Viscosity (23°C±0.5°C): min 0 - max 0

9.2. Other information

No further information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

TEAK 3

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

c) serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

6813.001/2

Page n. 7 of 12

Safety Data Sheet

TEAK 3

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

The product is classified: STOT RE 1 H372

j) aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 5000 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 3160 mg/kg

Test: LC50 - Route: inhalation - Species: rat > 1.58 mg/l

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LC50 - Route: inhalation - Species: rat = 17.2 mg/l - Duration: 4h

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 3500 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 4200 mg/kg

Test: LC50 - Route: inhalation of vapours - Species: rat > 20 ml/l

c) serious eye damage/irritation:

Test: Eye Irritant Positive

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

TEAK 3

The product is classified: Aquatic Chronic 2 - H411

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia = 2.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae 18204.2 5 mg/l - Duration h: 72

12.2. Persistence and degradability

There is no data available on the preparation itself.

N.A.

12.3. Bioaccumulative potential

There is no data available on the preparation itself.

N.A.

12.4. Mobility in soil

There is no data available on the preparation itself.

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

6813.001/2

Safety Data Sheet

TEAK 3

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Directives 91/156/CEE, 91/689/CEE, 94/62/CE.

EWG CODE 080111

Do not empty into drains, ground or waterways. Dispose of product residues and related containers at a collection point for hazardous or special waste or, where appropriate, through an authorized waste disposal company.

SECTION 14: Transport information

14.1. UN number

UN 1263

14.2 Proper shipping name: Paint.

14.3 Transport hazard class(es) and Packing Group:

3 PG III

14.4. Environmental hazards

Marine Pollutant: Yes

14.5. Special precautions for user

None

Other informations

Land transport ADR/RID

ADR Classification code: F1

Maximum quantity for Limited Quantities: 5L/Kg

Tunnel code :D/E

Transport category: 3

Maritime transport (IMDG)

Maximum quantity for Limited Quantities: 5L/Kg

EmS number: F-E/S-E

Stowage provisions: A

Air transport(IATA/ICAO)

Maximum quantity for Limited Quantities: 5L/Kg

Pkg. inst. passenger and cargo aircraft: 309

Pkg. inst. cargo aircraft only: 310

Erg-code: 3L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 89/391/CEE and subsequent amendments (Risks related to chemical agents at work and Occupational exposure limit values). Directive 1999/13/EC and subsequent amendments (limitation of emissions of volatile organic compounds due to the use of organic solvents in certain activities and installations). Regulation (CE) n. 1907/2006 , Regulation (CE) 830/2015 and subsequent amendments (concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals - REACH). Regulation (CE) n.1272/2008 and subsequent amendments (on classification, labeling and packaging of substances and mixtures - CLP). International Maritime Dangerous Goods Code, IATA Dangerous Goods Regulation, International Carriage of Dangerous Goods by Road (ADR).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restriction 3 is not applicable because the mixture does not fall within the restrictions mentioned

6813.001/2

Page n. 9 of 12

Safety Data Sheet

TEAK 3

in Annex XVII of EC Regulation No. 1907/2006.

Restriction 40 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Where applicable, refer to the following regulatory provisions :

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation UE No 649/2012 concerning the export and import of dangerous chemicals.

Regulation UE n. 528/2012 concerning the making available on the market and use of biocidal products.

Directive 2012/18/EU (Seveso III)

Regulation (EC) No. 648/2004 (detergents).

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation (EC) No 689/2006 concerning the export and import of dangerous chemicals.

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c, E2

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2

6813.001/2

Safety Data Sheet

TEAK 3

Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
-------------------	--------	--

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method
STOT RE 1, H372	Calculation method
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.

6813.001/2

Page n. 11 of 12

Safety Data Sheet

TEAK 3

KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.