



Safety Data Sheet

Copyright, 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	31-0130-0	Version number:	6.02
Revision date:	23/10/2019	Supersedes date:	29/07/2019
Transportation version number:	1.00 (22/04/2013)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

Product Identification Numbers

UU-0032-4265-6

7100077750

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Marine

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Sensitization, Category 1A - Skin Sens. 1A; H317
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Specific Target Organ Toxicity-Repeated Exposure, Category 1 - STOT RE 1; H372
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)		919-446-0	15 - 40
Alkyloammonium Salt	Trade Secret		1 - 5
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	911-418-6	< 0.002

HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.	
H336	May cause drowsiness or dizziness.	
H372	Causes damage to organs through prolonged or repeated exposure:	nervous system
H411	Toxic to aquatic life with long lasting effects.	

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P260A Do not breathe vapours.
P280E Wear protective gloves.
P273 Avoid release to the environment.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

2% of the mixture consists of components of unknown acute oral toxicity.

3% of the mixture consists of components of unknown acute inhalation toxicity.
 Contains 1% of components with unknown hazards to the aquatic environment.

Information required per Regulation (EU) No 528/2012 on Biocidal Products:

Contains a biocidal product (preservative): C(M)IT/MIT (3:1).

Notes on labelling

H304 is not required on the label due to the product's viscosity

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			15 - 40	Substance not classified as hazardous
Aluminium Oxide (non-fibrous)	1344-28-1	215-691-6	01-2119529248-35	15 - 40	Substance with a Community level exposure limit in the workplace
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)		919-446-0		15 - 40	Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; EUH066; STOT RE 1, H372
Sorbitan monooleate, ethoxylated	9005-65-6	500-019-9		5 - 10	Substance not classified as hazardous
White mineral oil (petroleum)	8042-47-5	232-455-8		1 - 5	Asp. Tox. 1, H304
Alkyloammonium Salt	Trade Secret			1 - 5	Skin Sens. 1B, H317
1,2,4-Trimethylbenzene	95-63-6	202-436-9		< 2	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 2, H411
Nonane	111-84-2	203-913-4		< 2	Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	911-418-6		< 0.002	EUH071; Acute Tox. 3, H301; Skin Corr. 1C, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=100; Aquatic Chronic 1, H410,M=100 - Nota B Acute Tox. 2, H330; Acute Tox. 2, H310

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
 Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium Oxide (non-fibrous)	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m ³ ;TWA(as respirable dust):4 mg/m ³	
Benzene, trimethyl-	95-63-6	UK HSC	TWA:125 mg/m ³ (25 ppm)	

UK HSC : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Colour

Liquid.
Off-White, White

Odor

Odour threshold

Slight Solvent
No data available.

pH

Boiling point/boiling range

7.3 - 8.5
100 °C [*Test Method: Estimated*]

Melting point

No data available.

Flammability (solid, gas)

Not applicable.

Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	Flash point > 93 °C (200 °F) [<i>Test Method</i> :Closed Cup]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	2,343.8 Pa [<i>Test Method</i> :Estimated] [<i>Details</i> :at 68 F]
Relative density	1.12 [<i>Ref Std</i> :WATER=1]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	35,000 - 45,000 mPa-s
Density	1.1 - 1.13 g/ml

9.2. Other information

EU Volatile Organic Compounds

No data available.

Percent volatile

63.4 % weight [*Test Method*:Estimated]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Central neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Dermal	Rat	LD50 > 3,400 mg/kg
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation-Vapour (4 hours)	Rat	LC50 > 16.2 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Ingestion	Rat	LD50 > 15,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Dermal	Not available	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

Sorbitan monooleate, ethoxylated	Ingestion	Rat	LD50 20,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapour (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg
Alkyloammonium Salt	Ingestion	Rat	LD50 > 5,385 mg/kg
Alkyloammonium Salt	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Rabbit	LD50 87 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Rabbit	Minimal irritation
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
1,2,4-Trimethylbenzene	Rabbit	Irritant
Alkyloammonium Salt	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Rabbit	No significant irritation
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
1,2,4-Trimethylbenzene	Rabbit	Mild irritant
Alkyloammonium Salt	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Guinea pig	Not classified
Sorbitan monooleate, ethoxylated	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
1,2,4-Trimethylbenzene	Guinea pig	Not classified
Alkyloammonium Salt	Mouse	Sensitising
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Sensitising

Photosensitisation

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

Name	Species	Value
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
Sorbitan monooleate, ethoxylated	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic
Alkyloammonium Salt	In Vitro	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Sorbitan monooleate, ethoxylated	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Mouse	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
1,2,4-Trimethylbenzene	Inhalation	Not classified for female reproduction	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Not classified for male reproduction	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 1.5 mg/l	during gestation

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

Alkyloammonium Salt	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Alkyloammonium Salt	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyloammonium Salt	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	gestation into lactation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,2,4-Trimethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation	central nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Sorbitan monooleate, ethoxylated	Ingestion	heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory	Not classified	Rat	NOAEL 4,132 mg/kg/day	90 days

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

		system				
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract immune system	Not classified	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 600 mg/kg/day	14 days
1,2,4-Trimethylbenzene	Ingestion	liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyloammonium Salt	Ingestion	hematopoietic system heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	35 days

Aspiration Hazard

Name	Value
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
1,2,4-Trimethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Aluminium Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	LC50	>100 mg/l

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Green algae	Estimated	72 hours	Effect Level 50%	4.1 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Rainbow trout	Estimated	96 hours	Lethal Level 50%	mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Water flea	Estimated	48 hours	Effect Level 50%	mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Green algae	Estimated	72 hours	No obs Effect Level	0.76 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Water flea	Estimated	21 days	Effect Concentration 10%	0.316 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Copepods	Estimated	48 hours	Lethal Level 50%	>10,000 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Green Algae	Estimated	72 hours	Effect Level 50%	58.84 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Green Algae	Estimated	72 hours	Effect Concentration 10%	19.05 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Water flea	Estimated	21 days	No obs Effect Level	10 mg/l
Alkyloammonium Salt	Trade Secret	Green Algae	Experimental	72 hours	Effect Level 50%	105 mg/l
Alkyloammonium Salt	Trade Secret	Rainbow trout	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Alkyloammonium Salt	Trade Secret	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Alkyloammonium Salt	Trade Secret	Green Algae	Experimental	72 hours	Effect Level 10%	40 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
1,2,4-Trimethylbenzene	95-63-6	Fathead minnow	Experimental	96 hours	LC50	7.72 mg/l
1,2,4-Trimethylbenzene	95-63-6	Mysid Shrimp	Experimental	96 hours	LC50	2 mg/l
1,2,4-Trimethylbenzene	95-63-6	Water flea	Experimental	48 hours	EC50	3.6 mg/l
Nonane	111-84-2	Water flea	Experimental	48 hours	EC50	0.2 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Copepods	Experimental	48 hours	EC50	0.007 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	EC50	0.0199 mg/l

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Green Algae	Experimental	72 hours	EC50	0.027 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Rainbow trout	Experimental	96 hours	LC50	0.19 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Sheepshead Minnow	Experimental	96 hours	LC50	0.3 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Water flea	Experimental	48 hours	EC50	0.099 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	48 hours	NOEC	0.00049 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Fathead minnow	Experimental	36 days	No obs Effect Level	0.02 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Green Algae	Experimental	72 hours	NOEC	0.004 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Water flea	Experimental	21 days	NOEC	0.004 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not availbl-insufficient			N/A	
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Estimated Biodegradation	28 days	BOD	75 % BOD/ThBOD	OECD 301F - Manometric respirometry
Sorbitan monooleate, ethoxylated	9005-65-6	Experimental Biodegradation	28 days	CO2 evolution	61 % weight	Other methods
Alkyloammonium Salt	Trade Secret	Experimental Biodegradation	28 days	BOD	23 % BOD/ThBOD	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
1,2,4-Trimethylbenzene	95-63-6	Experimental Photolysis		Photolytic half-life (in air)	11.8 hours (t 1/2)	Other methods
1,2,4-Trimethylbenzene	95-63-6	Experimental Biodegradation	28 days	BOD	>60 % weight	OECD 301F - Manometric respirometry
Nonane	111-84-2	Experimental Photolysis		Photolytic half-life (in air)	3.07 days (t 1/2)	Other methods
Nonane	111-84-2	Experimental Biodegradation	28 days	BOD	96 % weight	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Estimated Photolysis		Photolytic half-life (in air)	1.2 days (t 1/2)	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Experimental Hydrolysis		Hydrolytic half-life	> 60 days (t 1/2)	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Estimated Biodegradation	29 days	CO2 evolution	62 %CO2 evolution/THC O2 evolution (does not pass	OECD 301B - Modified sturm or CO2

3M™ Marine Compound and Finishing Material, 06044, 06045, 06046, 06044E

					10-day window)	
--	--	--	--	--	----------------	--

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sorbitan monooleate, ethoxylated	9005-65-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Alkyloammonium Salt	Trade Secret	Experimental Bioconcentration		Log Kow	< 1	Other methods
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2,4-Trimethylbenzene	95-63-6	Experimental BCF-Carp	56 days	Bioaccumulation factor	≤275	OECD 305E - Bioaccumulation flow-through fish test
Nonane	111-84-2	Experimental Bioconcentration		Log Kow	5.65	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Estimated BCF - Bluegill	28 days	Bioaccumulation factor	54	OECD 305E - Bioaccumulation flow-through fish test

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

UU-0032-4265-6

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Section 3: Composition/ Information of ingredients table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 16: UK disclaimer information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to

satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk