

*AIRMAR certifies that the application of Foulfree™ coating on its transducers results in no loss in transducer performance.

Section 1 - Identification of the Material and the Supplier

1.1 Product identifier

Product name	XDclean
Catalog No.	LCW Component in Foulfree kit FF15K.
CAS No.	540-88-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Protective coating for transducers
Restrictions of use	Refer to Section 15

1.3 Details of the supplier of the Safety Data Sheet

Supplier Propspeed International Ltd
PO Box 83232
Edmonton
Auckland
New Zealand
www.propspeed.com

Telephone +64 9 524 1470
Telefax +64 9 813 5246

E-mail (competent person) info@propspeed.com

1.4 Emergency telephone number

Emergency number	New Zealand	0800 243 622
(24h/24 – 365 d/year)	Australian	1800 127 406
	Global Access	+ 64 4 917 988

NZ National Poisons Centre Telephone +64 4 917 9888 (ChemCall)

Section 2 - Hazards identification

2.1 GHS Classification

Flammable liquids	Category 2
Acute toxicity; Inhalation	Category 4
Specific target organ toxicity - single exposure	Category 3

2.2 GHS labeling

Symbols:



GHS Signal word: **Danger**

Hazard statements:

[H-Code: Hazard information]

H225: Highly flammable liquid and vapour.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

Precautionary statements:

[P-Code: Safety information]

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ ventilating/ lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P303 + P361 + P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor if you feel unwell.

Storage

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal

P501: Dispose of contents/container to an approved waste disposal plant.

2.3 Other hazards

Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition/information on ingredients

3.1 Substances

Chemical nature: Substance

Component

Ingredient name	CAS No. EC-No.	Weight%	Component type
Tert-Butyl acetate	540-88-5	> 99.5 %	Substance
t-Butyl Alcohol	75-65-0	< 0.5 %	Impurity
2,4,4-Trimethyl-1-pentene	107-39-1	< 0.5 %	Impurity

Section 4 - First aid measures

4.1 Description of first aid measures

General information:

Consult a physician/doctor if necessary. Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Show this material safety data sheet to the doctor in attendance.

Following inhalation:

If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Call a physician.

Following skin contact:

Remove contaminated clothing as needed. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. If sticky, use waterless cleaner first. Seek medical attention if ill effect or irritation develops.

Following eye contact:

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

Following ingestion:

If large quantity swallowed, give lukewarm water (pint/ 1/2 liter) if victim completely conscious/alert. Do not induce vomiting. Risk of damage to lungs exceeds poisoning risk. Obtain emergency medical attention.

Notes to physician:

Symptoms

If inhalation occurs signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever.

High doses may cause CNS depression (fatigue, dizziness and possibly loss of concentration, with collapse, coma and death in cases of severe over-exposure).

The onset of respiratory symptoms may be delayed for several hours after exposure.

Hazards

May be harmful if swallowed and enters airways.

May be harmful if swallowed.

Harmful if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Treatment

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5 – Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

SMALL FIRE: Use dry chemicals, CO₂, water spray or alcohol-resistant foam. LARGE FIRE: Use water spray, water fog or alcohol-resistant foam.

Unsuitable extinguishing media:

Do not use solid water stream - may spread fire.

5.2 Special hazards arising from the substance or mixture

Releases flammable vapours below normal ambient temperatures.

When mixed with air and exposed to ignition source, vapours can burn in open or explode if confined.

Flammable vapours may be heavier than air and travel long distances along the ground before igniting and flashing back to vapor source.

Move containers from fire area if it can be done without risk.

Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

Cool containers with flooding quantities of water until well after fire is out.

Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
Always stay away from tanks engulfed in fire.

For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

5.3 Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Structural firefighter's protective clothing will only provide limited protection.

5.4 Further information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored separately in closed containments.

Use a water spray to cool fully closed containers.

5.5 Hazchem Code

3YE

Section 6 - Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation.

6.2 Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Extremely flammable. Eliminate all sources of ignition. All equipment used when handling this product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapours. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. Dike large spills and place materials in salvage containers. Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.4 Additional advice

See section 8 for PPE information.

Section 7 - Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

- Use only non-sparking tools.
- Extinguish all ignition sources.
- Carefully vent any internal pressure before removing closure.
- Containers must be properly grounded before beginning transfer.
- Handle empty containers with care; vapor/residue may be flammable.
- All equipment must conform to applicable electrical code.
- This material may attack some forms of plastics, rubbers, and coatings.
- Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair.
- Check atmosphere for explosiveness and oxygen deficiencies.
- Wear recommended personal protective equipment.
- Observe precautions pertaining to confined space entry.
- Do not breathe vapours or spray mist.

Advice on protection against fire and explosion

- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Take precautionary measures against static discharge.

Fire-fighting class

- Highly flammable liquid.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

- Store closed drums with bung in up position.
- Store only in tightly closed, properly vented containers away from heat, sparks, open flame and strong oxidizing agents.
- Containers must be properly grounded before beginning transfer.
- This material may attack some forms of plastics, rubbers, and coatings.
- Consult supplier(s) of these materials for specific recommendations.
- Steel drums are recommended for packaging.

7.3 Specific end use(s)

See Section 1.

Section 8 - Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Occupational exposure limit values (WELs)

Components	CAS-No.	Type	Limit Value	Basis Revision Date
Tert-Butyl Acetate	540-88-5	TWA	200 ppm 950 mg/m ³	NOHSC (AU) August 31, 2005
t-Butyl Alcohol	75-65-0	TWA	100 ppm	US (ACGIH) 2012
t-Butyl Alcohol	75-65-0	TWA	150 ppm 455 mg/m ³	NOHSC (AU) August 31, 2005
t-Butyl Alcohol	75-65-0	TWA	100 ppm 303 mg/m ³	NOHSC (AU) August 31, 2005

Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

Both local exhaust and good general room ventilation must be provided not only to control exposure but also to prevent formation of flammable mixtures.

Personal protective equipment

Respiratory protection

If exposure can potentially exceed the exposure limit(s), respiratory protection recommended or approved by appropriate local, state or international agency must be used.

Hand protection

Wear chemical resistant gloves such as:
Butyl rubber.

Eye/face protection

Use splash goggles when eye contact due to splashing or spraying liquid is possible.

Skin and body protection

Depending on the conditions of use, protective gloves, apron, boots, head and face protection should be worn.

The equipment must be cleaned thoroughly after each use.

Hygiene measures

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Emergency eye wash fountains and safety showers should be available in the

immediate vicinity of any potential exposure.

Use good personal hygiene practices.

Wash hands before eating, drinking, smoking, or using toilet facilities.

Wash clothing frequently.

Section 9 – Physical and chemical properties

Appearance	liquid
Colour	clear, colourless
Odour	camphor-like-odor
Odour threshold	8 ppb
Flash point	4 °C at 1,013.0 hPa (759.8 mm Hg)
Ignition temperature	589 °C at 1,013 hPa
Lower explosion limit	= 1.26 vol %
Upper explosion limit	= 6.88 vol %
Flammability (solid, gas)	Not applicable
Oxidizing properties	Not considered an oxidizing agent
Auto-ignition temperature	589 °C at 1,013 hPa
Molecular weight	116.16 g/mol
Decomposition temperature	not determined
pH	6 - 7
Melting point /freezing point	-58.15 °C at 1,013 hPa
Boiling point and boiling range	97.8 °C at 1,013 hPa
Flash point	16.6 °C – 22.2 °C
Vapour pressure	55.995 hPa at 20 °C
Density	0.86 g/cm ³ at 25 °C
Water solubility	7,820 mg/L at 23 °C
Partition coefficient (n-octanol/water)	1.64 (Log Pow) at 21.7 °C
Viscosity, dynamic	< 1 mPa.s at 25 °C
Viscosity, kinematic	< 1 mm ² /s
Relative vapour density	No data available
Evaporation rate	2.8 (butyl acetate = 1)
Explosive properties	Not explosive
Other information	Additional properties may be listed in Sections 2 and 5

Section 10 – Stability and reactivity

10.1 Reactivity

Will not occur.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Not expected to occur.

10.4 Conditions to avoid

Heat, sparks, open flame, other ignition sources, and oxidizing conditions.

10.5 Material to avoid

Some plastics.

Acids.

Alkalies.

Nitrates.

Strong oxidizing agents.

10.6 Hazardous decomposition products

Under hot, acidic conditions, the decomposition products are isobutylene and acetic acid.

Thermal decomposition Carbon oxides (CO, CO₂), Water.

Section 11 – Toxicological information

Product Summary

The below given information is based on the assessment of the product including impurities.

Acute toxicity

Acute oral toxicity

Based on acute toxicity values, not classified.
May be harmful if swallowed.

High doses may cause CNS depression (fatigue, dizziness and possibly loss of concentration, with collapse, coma and death in cases of severe over-exposure).

LD50 Oral: 4,500 mg/kg

Acute inhalation toxicity

Classified
Harmful if inhaled.

High vapor concentrations may cause CNS stimulation (increased activity, shaking, tremors) and/or depression (fatigue, dizziness, and possibly loss of concentration, with collapse, coma and death in cases of severe over-exposure).

LC50: 12.52 mg/l
Exposure time: 4 HOURS
Method: Calculation method

Acute dermal toxicity

Based on acute toxicity values, not classified.
LD50 Dermal: > 2,000 mg/kg

Skin corrosion/irritation

Based on skin irritation values, not classified.
May cause slight transient skin irritation.
Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on eye irritation values, not classified.
Moderate eye irritation

Respiratory or skin sensitization

Respiratory sensitization
Not classified
No study available.
Skin sensitization
Not classified
No adverse effect observed

Chronic toxicity

Carcinogenicity

Not classified
No adverse effect observed

Germ cell mutagenicity

Not classified
No adverse effect observed.

Reproductive toxicity

Effects on fertility /
Effects on or via lactation

Not classified
Effects on or via lactation No adverse effect observed

Effects on
Development

Not classified
No adverse effect observed

**Target Organ
Systemic Toxicant -
Single exposure**

Classified, may cause respiratory irritation.

May cause drowsiness or dizziness.

Exposure routes: Inhalation, Ingestion

Target Organs: Central nervous system, Respiratory system

**Target Organ
Systemic Toxicant -
Repeated exposure**

Based on repeated exposure toxicity values, not classified.

Aspiration hazard

Not classified
May be harmful if swallowed and enters airways.

Section 12 – Ecological information

Environmental Assessment

Short-term (acute) aquatic hazard

Harmful to aquatic life.

Long-term (chronic) aquatic hazard

Not classified, based on readily biodegradability and low acute toxicity.

Toxicity to fish

Low acute toxicity to fish

Toxicity to daphnia and other aquatic invertebrates

Low acute toxicity to aquatic invertebrates.

Toxicity to algae

Harmful to algae.
Can inhibit growth of aquatic algae

EC50: 16 mg/l

Exposure time: 72 HOURS

Species: Pseudokirchneriella subcapitata (green algae)

Test type: Growth inhibition

EC50: 64 mg/l

Exposure time: 96 HOURS

NOEC: 2.3 mg/l

Toxicity to bacteria

High concentrations may be harmful to sewage treatment plant microbes

1.5 mg/l

Species: Activated sludge

Test type: Respiration inhibition

Toxicity to fish (Chronic toxicity)

no data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

no data available

Persistence and degradability

Biodegradability

Biodegradation: 50 %

Inherently biodegradable.

(After 28 days in a ready biodegradability test)

Stability in water

tert-butyl acetate

tert-butyl alcohol

Hydrolyzes slowly.

Hydrolytically stable.

Stability in soil

tert-butyl acetate

tert-butyl alcohol

2,4,4-trimethylpent-1-ene

Low potential for soil adsorption expected

Low potential for soil adsorption expected

Expected to have moderate mobility in soils.

Volatilization from moist soil surfaces is expected to be an important fate process of this material.

The potential for volatilization from dry soil surfaces may exist.

Not likely to adsorb to suspended solids and sediment in water.

Bioaccumulative potential

Bioaccumulation

Bioconcentration factor (BCF): 6.7

This material is not expected to bioaccumulate.

Mobility in soil

Distribution among environmental compartments

tert-butyl acetate

Released material would be expected to show high soil mobility and to volatilize readily from soil and surface waters, forming atmospheric vapor.

Other adverse effects

Environmental fate and pathways

No additional information available.

Other information

Additional ecological information

No additional information available.

Section 13 – Disposal considerations

13.1 Waste treatment methods

Product

Contaminated product, soil, water, container residues and spill clean up materials may be hazardous wastes.

Comply with applicable federal, state, and local regulations.

Section 14 – Transport information

ADG

UN number	1123
Description of the goods	BUTYL ACETATES
Class	3
Packing group	II
Labels	3
Hazchem Code	3YE

IMDG

UN number	1123
Description of the goods	BUTYL ACETATES
Class	3
Packing group	II
Labels	3
EmS Number 1	F-E
EmS Number 2	S-D
Marine pollutant	No

BLG (MARPOL Annex II) Description of the goods Pollution category Ship type	BUTYL ACETATE (ALL ISOMERS) Y 3
IATA UN number Description of the goods Class Packing group Labels	1123 BUTYL ACETATES (Tert-Butyl acetate) 3 II 3

Section 15 – Regulatory information

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
USA	TSCA	Compliant
Taiwan	TCSCA	Compliant

Section 16 – Other information

Product

The information provided in this document is based on our knowledge at the date of its publication. The properties of the product described do not constitute a warranty in the legal sense of the term. The provision of this document does not release the purchaser of the product from his responsibility to comply with legislations and regulations in force for this product. This statement applies for the resale and distribution of the product, or of substances or goods containing this

product, in other jurisdictions and having regard to the industrial and commercial property rights of third parties. If the product described is transformed or mixed with other substances or materials, the information contained in this document may not be valid for the new product thus manufactured, unless explicitly mentioned. In case of repackaging of the product, the customer is required to provide the required safety information.

Legend

CAS	Chemical Abstracts Service
ppm	part per million
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
EC50	Effective Concentration 50%
vPvB	very Persistent and very Bioaccumulative
WEL	Workplace Exposure Limit
PBT	Persistent, Bioaccumulative and Toxic
DNEL	Derived No-Effect Level
PNEC	Predicted No-Effect Concentration
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemical
CLP	Regulation on Classification, Labelling and Packaging of substances and mixtures
ADR/RID	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association

Flam. Liq. Flammable liquid

Acute Tox. Acute toxicity