


The product is designed, manufactured and tested in according to 97/23/EC directive and meets the applicable requirements listed below

	<p align="center">ATX1</p> <p align="center">PART NUMBER 16508010</p>	<p align="center">ATX2</p> <p align="center">PART NUMBER 16508110</p>
<p align="center">VOLUME</p>	<p align="center">0,5 L</p>	<p align="center">2 L</p>
<p align="center">FLUID PRESSURE</p>	<p align="center">10 bar (max)</p>	<p align="center">10 bar (max)</p>
<p align="center">AIR PRESSURE</p>	<p align="center">6 bar (max)</p>	<p align="center">6 bar (max)</p>
<p align="center">TEST PRESSURE</p>	<p align="center">14,3 bar</p>	<p align="center">14,3 bar</p>
<p align="center">DESIGN TEMPERATURE</p>	<p align="center">-10/+99 °C</p>	<p align="center">-10/+99°C</p>
<p align="center">PORTS</p>	<p align="center">T 3/8" BSP</p>	<p align="center">T 1/2" BSP</p>
<p align="center">MEMBRANE MATERIAL</p>	<p align="center">Butyl rubber</p>	<p align="center">Butyl rubber</p>
<p align="center">FLUID GROUP</p>	<p align="center">2</p>	<p align="center">2</p>
<p align="center">CONFORMITY ASSESSMENT PROCEDURES</p>	<p align="center">CAT I Mod. A</p>	<p align="center">CAT I Mod. A</p>
<p align="center">DIMENSIONS</p>	<p align="center">Ø 95 mm x 202 mm (L)</p>	<p align="center">Ø 138 mm x 274 mm (L)</p>