

Technical Data Sheet

04. Sep. 2015 / Rev No. (1)

1. Product and Introduction

X313T

| Product Name | X313T | | | | |
|---------------------|------------------|--|--|--|--|
| Backing Material | Knitted Fabric | | | | |
| Bonding | Resin over Resin | | | | |
| Mineral Type | Aluminum Oxide | | | | |
| Coating State | _ | | | | |
| Manufacturing Width | 1340mm | | | | |

2. Available Grit

| Grit | 16 | 24 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 |
|------|-----|-------------|-----|-------------|-----|-------------|-----|-------------|------|-------------|------|-------------|
| | | | | | | | • | \triangle | • | \triangle | • | \triangle |
| | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 |
| | • | \triangle | • | \triangle | • | \triangle | • | | | | | |

[◀] Rough(Grinding)

Finishing (Polishing) ▶

3. Advantage

- ◆ High cutting performance without clogging.
- ♦ Good sharpness.
- ♦ Long life time.
- Good for dust suction.

4. Operation / Application

- ♦ Discs, Sheet.
- ♦ Wood working, Casting, Plastic, etc.

5. Work pieces

- ◆ Nonferrous(Al, Zn, etc).
- Common painted surface.
- ◆ Wood (solid & Painted).

6. Available Sander / Grinder

◆ Vibrator.

Orbital sander.

♦ Manual sanding.

628-4, Seonggok-dong, Ansan, Gyeonggi-do, Korea www.sunmight.com

⁻ Introductory Remarks ●: Standard Grit △: Non Standard Grit